



Battery Range Summary

Genesis® NP batteries feature heavy duty thick lead-calcium grids for years of dependable performance. The high energy density design, factory sealed case and leak-proof construction ensures that these rechargeable sealed lead acid batteries are extremely reliable and virtually maintenance-free.

The batteries are completely sealed by the factory, meaning zero watering requirements. The Genesis NP battery design includes a low pressure relief valve to release any build-up of pressure within the case. This vent is completely self-resealing ensuring the highest possible rate of internal recombination is reached within each battery.

With an expected life span of three to five years in float applications at 77°F (25°C) ambient temperature, more than 1,000 discharge/recharge cycles can be realized depending on the DOD for each cycle. The internal grid design has been perfected over 10 decades of battery experience to yield a battery that can recover even after repeated deep discharges.

Features and Benefits

- Capacity range 1- 200Ah
- Lead calcium alloy
- Sealed design, no watering required
- 1,000+ cycles can be realized depending on Depth of Discharge (DOD)
- Heavy duty grids maximize life
- Three to five year life expectancy in float applications at 77°F (25°C) ambient temperature

Construction

- Heavy duty thick lead-calcium grids
- Sealed case for leak-proof operation
- Designed to promote internal recombination for longer life
- Integral pressure relief valve operates at 2-3 PSI and is self-resealing
- Flame retardant UL94-V0 case and cover available

Installation and Operation

- Space efficient footprint
- Compact, quick and simple installation process
- Three to five year life expectancy in float applications at 77°F (25°C) ambient temperature
- Low maintenance - no watering required
- Operating temperature: -5°F (-15°C) to 122°F (50°C); Recommended temperature: 68°F (20°C) to 86°F (30°C)

Standards

- Approved for air transportation (IATA A67)
- Recognized by UL File no. MH16464 and MH15740
- Non-spillable classification (UN2800)
- IEC 61056-1, IEC 60896-21 and IEC60896-22 compliant

General Specifications

Genesis® NP Battery Series

Battery Type	FR Battery Type*	Volts	Nominal Capacity 20hr rate-Ah ¹	Nominal Dimensions						Typical Weight		Layout	Terminal Illustration	Electrolyte (1.300 SG)				Internal Resistance (mΩ)	Short Circuit (A)
				Length		Width		Height ‡		lbs	kg			Volume		Volume			
				in	mm	in	mm	in	mm					gal	L	lbs	kg		
NP1.2-6	n/a	6	1.2	3.82	97	0.98	25	2.20	56	0.67	0.30	1	A	0.014	0.053	0.152	0.069	-	-
NP4-6	n/a	6	4.0	2.76	70	1.85	47	4.15	105	1.76	0.80	5	A	0.038	0.144	0.412	0.187	20	315
NP4.5-6	n/a	6	4.5	2.76	70	1.85	47	4.15	105	1.80	0.82	5	A	0.040	0.151	0.433	0.196	19	330
NP5-6	n/a	6	5.0	2.76	70	1.85	47	4.15	105	1.83	0.83	5	A	0.046	0.172	0.493	0.223	18	350
NP7-6	n/a	6	7.0	5.95	151	1.30	33	3.94	100	2.76	1.25	1	A	0.065	0.246	0.704	0.319	15	415
NP7-6T	n/a	6	7.0	5.95	151	1.30	33	3.94	100	2.76	1.25	1	C	0.065	0.246	0.704	0.319	15	415
NP10-6	n/a	6	10.0	5.95	151	1.97	50	3.98	101	3.81	1.73	1	A	0.100	0.379	1.08	0.491	10	625
NP12-6	n/a	6	12.0	5.95	151	1.97	50	3.98	101	4.23	1.92	1	A	0.100	0.379	1.08	0.491	8	780
NP0.8-12	n/a	12	0.8	3.78	96	0.98	25	2.42	61	0.82	0.37	6	H	0.013	0.049	0.14	0.064	180	70
NP1.2-12	n/a	12	1.2	3.82	97	1.89	48	2.20	56	1.25	0.57	3	A	0.025	0.095	0.27	0.123	120	105
NP2-12	n/a	12	2.0	5.91	150	0.79	20	3.50	89	1.54	0.70	7	B	0.034	0.129	0.37	0.167	80	155
n/a	NP2.3-12FR	12	2.3	7.01	178	1.38	35	2.64	67	2.23	1.01	1	A	0.036	0.136	0.39	0.177	65	190
n/a	NP2.6-12FR	12	2.6	5.28	134	2.64	67	2.60	66	2.79	1.27	3	A	0.045	0.170	0.49	0.221	60	210
NP2.9-12	n/a	12	2.9	3.11	79	2.20	56	4.13	105	2.73	1.24	1	A	0.053	0.201	0.57	0.260	57	220
NP3.4-12	n/a	12	3.4	5.28	134	2.64	67	2.64	67	3.06	1.39	3	A	0.059	0.223	0.64	0.290	45	280
NP4-12	n/a	12	4.0	3.54	90	2.76	70	4.21	107	3.74	1.70	1	A	0.075	0.284	0.81	0.368	38	330
NP5-12	n/a	12	5.0	3.54	90	2.76	70	4.21	107	3.88	1.76	1	A	0.085	0.322	0.92	0.417	35	355
NP5-12T	n/a	12	5.0	3.54	90	2.76	70	4.21	107	3.88	1.76	1	C	0.085	0.322	0.92	0.417	35	355
NP7-12	NP7-12FR	12	7.0	5.95	151	2.56	65	3.94	100	5.29	2.40	4	A	0.120	0.454	1.30	0.589	30	415
NP7-12T	NP7-12TFR	12	7.0	5.95	151	2.56	65	3.94	100	5.29	2.40	4	C	0.120	0.454	1.30	0.589	30	415
NP9-12T	NP9-12TFR	12	9.0**	5.95	151	2.56	65	3.94	100	5.94	2.69	4	C	0.148	0.560	1.60	0.726	14	650
NP12-12T	NP12-12TFR	12	12.0	5.95	151	3.86	98	3.94	100	8.26	3.75	4	C	0.180	0.681	1.95	0.884	16	780
NP18-12B	NP18-12BFR	12	17.2	7.13	181	3.00	76	6.57	167	13.6	6.17	2	D	0.280	1.06	3.03	1.38	13	960
n/a	NP24-12BFR	12	24.0	6.54	166	6.89	175	4.92	125	20.0	9.07	2	D	0.430	1.63	4.66	2.11	10	1250
n/a	NP24-12TFR	12	24.0	6.54	166	6.89	175	4.92	125	20.0	9.07	2	C	0.430	1.63	4.66	2.11	10	1250
n/a	NP33-12BFR	12	33.0	7.76	197	5.16	131	6.22‡	158‡	25.1	11.39	1	F	0.480	1.82	5.20	2.36	9	1440
n/a	NP38-12BFR	12	38.0	7.76	197	6.50	165	6.77	172	29.8	143.5	2	F	0.680	2.57	7.36	3.34	8	1565
n/a	NP55-12BFR	12	55.0	9.02	229	5.43	138	8.15‡	207‡	40.8	18.50	1	J	0.850	3.22	9.21	4.17	8	1605

¹ Amp Hour rate is subject to change without notice.

* FR: UL94-V0, Flame Retardant Case and Cover (Oxygen index 28)

** Nominal capacity 10hr rate-Ah

‡ Height is top cover. Overall height, including terminal is dependent on the terminal configuration.

Note: All dimensions are +/- 0.08 inches (2mm); Weights are +/- 5%

Torque Specifications:

M5 Bolt: 26.6 lbf.in (3Nm) +/- 5%

M6 Bolt: 44.31 lbf.in (5Nm) +/- 5%

M5 Receptacle: 35.4 lbf.in (4Nm) +/- 5%

M6 Receptacle: 65 lbf.in (6.8Nm) +/- 5%

General Specifications Continued

DataSafe® NPX Battery Series

Battery Type	FR Battery Type*	Volts	Watts/Cell to 1.67 End Voltage	Nominal Capacity 20hr rate-Ah ¹	Nominal Dimensions						Typical Weight		Layout	Terminal Illustration	Electrolyte (1.300 SG)				Internal Resistance (mΩ)	Short Circuit (A)
					Length		Width		Height ‡		lbs	kg			Volume gal	Volume L	Volume lbs	Volume kg		
n/a	NPX-50TFR	6	50W/Cell	13	5.95	151	1.97	50	3.94	100	4.60	2.09	1	C	0.070	0.265	0.758	0.344	12.2	720
n/a	NPX-25TFR	12	23W/Cell	5	3.54	90	2.75	70	4.21	107	4.30	1.95	1	C	0.065	0.246	0.704	0.319	16.5	300
n/a	NPX-35FR	12	35W/Cell	8	5.95	151	2.56	65	3.94	100	6.06	2.75	4	A	0.102	0.386	1.10	0.501	13.2	500
n/a	NPX-35TFR	12	35W/Cell	8	5.95	151	2.56	65	3.94	100	6.06	2.75	4	C	0.102	0.386	1.10	0.501	13.2	500
n/a	NPX-80BFR	12	80W/Cell	20	7.13	181	2.39	76	6.57	167	13.87	6.29	2	D	0.250	0.946	2.71	1.23	8.5	1000
n/a	NPX-80RFR	12	80W/Cell	20	7.13	181	2.39	76	6.57	167	13.87	6.29	2	E	0.250	0.946	2.71	1.23	8.5	1000
n/a	NPX-100RFR	12	95W/Cell	28	6.54	166	4.92	125	6.89	175	21.38	9.70	2	E	0.375	1.42	4.06	1.84	7.1	1500
n/a	NPX-150RFR	12	150W/Cell	40	7.76	197	6.50	165	6.77	172	31.50	14.29	2	G	0.570	2.16	6.17	2.80	5.0	2400


¹ Amp Hour rate is subject to change without notice.* FR: UL94-V0, Flame Retardant Case and Cover (Oxygen index 28)
 ‡ Height is top cover. Overall height, including terminal is dependent on the terminal configuration.
 Note: All dimensions are +/- 0.08 inches (2mm); Weights are +/- 5%

Torque Specifications:
 M5 Bolt: 26.6 lbf.in (3Nm) +/- 5%
 M6 Bolt: 44.31 lbf.in (5Nm) +/- 5%
 M5 Receptacle: 35.4 lbf.in (4Nm) +/- 5%
 M6 Receptacle: 65 lbf.in (6.8Nm) +/- 5%

Terminal Illustrations

<p>A</p>	<p>B</p>	<p>C</p>	<p>D</p>				
<p>Faston Tab 187</p>		<p>Faston Tab: 187 (F1)</p>		<p>"T" Faston Tab: 250 (F2)</p>		<p>"B" M5 Bolt Fastened Terminal</p>	
<p>E</p>	<p>F</p>	<p>G</p>	<p>H</p>				
<p>"R" M5 Threaded Receptacle</p>		<p>"B" M6 Bolt Fastened Terminal</p>		<p>"R" M6 Threaded Receptacle</p>		<p>JST No. VHR-2N</p>	
<p>J</p>		<p>Part Number Reference: "T" = 0.250 in wide (reference C) "R" = Receptacle (reference E and G) "B" = Bolt-On (reference D, F and J) "W" = Wide (reference I)</p> <p>Terminal Tolerances are: ±0.02 in. for dimensions < 5mm ±0.04 in. for dimensions ≥ 5mm ±0.08 in. for all height dimensions unless otherwise specified</p>					
<p>"B" M8 "Universal" Bolt Fastened Terminal</p>							

Layout Illustrations



Charging

- Standby use: Apply constant voltage charging at 2.28 volts per cell (or 2.25-2.30Vpc)
- Cyclic use: Apply constant voltage charging at 2.40-2.50 Vpc. Initial charging current should be set at less than 0.25CA
- Top charge: Product in storage (ambient temperature 77°F (25°C)) requires a top charge every six months. Apply constant voltage at 2.40 Vpc, initial charging should be set at less than 0.1CA for 15-20 hours

Temperature

- Keep within ambient temperatures of 5°F (-15°C) to 122°F (50°C) for both charging and discharging

Discharge

- Stop operation when voltage has reached the minimum permissible voltage per cell*. Recharge immediately
- Do not operate at 6CA or more current continuously

*Reference EnerSys Publication No. US-NP-AM

Incorporating Battery into Equipment

- Encase battery in a well ventilated compartment
- Avoid installing battery near heated units such as transformer
- House the battery in the lowest section of the equipment enclosure or rack to prevent unnecessary battery temperature rise

Storage

- Always store battery in a fully charged condition
- If battery is to be stored for a long period, apply a recovery top-charge every 6 months
- Store batteries in a dry and cool location

Others

- Avoid terminal short circuit
- DO NOT expose to open flame
- **WARNING:** Avoid exposure of the battery to any type of oil, solvent, detergent, petroleum-based solvent or ammonia solutions. These materials could potentially cause permanent damage to the battery jar and cover and will void the warranty



EnerSys World Headquarters
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-610-208-1991 /
+1-800-538-3627

EnerSys EMEA
EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

EnerSys Asia
No. 85, Tuas Avenue 1
Singapore 639518
Tel: +65 6558 7333